

Industrial Wet/Dry Vacs

2 & 3-Motor, 120V

216 - 315 CFM # 92" - 140" (H20

Div of Scott Electric • 4120-605-2992, #Direct

Multi-Use # Fine Dust # Sludge # Grease # Slurry

X-POWERFUL SUCTION # LARGER COLLECTION YIELDS — All models with wet/dry filters, complete tool kits, 2-year warranty.

Free Shipping on 2-Vacs

CS1600S — 2-Motor, 15.0 Gal Compact Tank on Tip'Pour Cart, 120V, 2-Stage Motors: 216 CFM, 72" H20

Power: Performance:

Filtration:

\$999.00

Size: Equipment:

- 120 Volt, 800 Watt Motors (2) ~ Low amp draw, high efficiency operates from a 15-amp circuit
- Holds over 60 lbs. of silica dust ~ A+ size and weight for use on scaffold (i.e. tuck pointing)
- Cyclonic separation with high efficiency (HE) cone filter, separates debris from air stream. Includes Dacron Cover to protect the HE filter by shedding dust, washable; Pre-Filter Air Pulse Vac Bag (5), keeps the HE primary filter and Dacron bag clean; Air Pulse Bag w/ "Zipper"(1); Float Shut-Off System for wet extraction.

21.5" x 23.5" x 38", Weight: 47 lbs.

• 1.5" x 10' hose w/ 2" ID smooth cuff, professional 8-pc wand and nozzle kit.

2-Year Warranty.

CS1700 — 2-Motor, 22.0 Gal HD Poly Tank, 120V, 2-Stage Motors: 216 CFM, 116" H20



Power:

 120 Volt, 8.50 Amp Motors (2) ~ Low amp draw, high efficiency motors – operate both motors from a 15-amp circuit

Performance:

 Rugged 22 gallon HD polyethylene tank resists cracking, denting and rusting

\$899.00

- Compact vacuum with quiet motors and independent on/off switches
- Includes 26" squeegee (right) with rubber blades for water and slurry pick-up — with or without the squeegee, maneuvering the vacuum is child's play

• Easy to empty: use the 1.5" x 3' drain hose or simply tilt backwards.

Filtration:

- Cyclone deflector, cone filter, Dacron cover (protects the cone filter, sheds fine dust and liquids), cone filter & Dacron cover are washable.
- Air Pulse Collection Bag (5) pre-filter for ultra fine dust, keeps the above filters clean
- Wet Filter with Float Shut-Off System the above filters are removed

Size:

• 21.5" x 23.5" x 38", Weight: 47 lbs.

Equipment:

• 1.5" x 10' hose w/ 2" ID smooth cuff, professional floor sweep tool kit (right), 26" tank mount squeegee, 3' flexible drain hose, Air Pulse Self-Clean Vac Bags (5).



CS1700S — 2-Motor, 18.0 Gal Metal Tank, 120V, 2-Stage Motors: 216 CFM, 116" H20

- Identical Specs, Power, Performance, Size, Filters, Equipment to the above CS1700.
- Difference: 18.0 gallon chrome plated HD metal tank on a powder coated tipping cart, no tank mounted squeegee.

\$849.00

CS235 — 2-Motor, 15.8 Gal, 120V, Flow Mix Head: 235 CFM or 140" H20



Power:

Performance:

Filtration:

Size:

• Slide the Flow Mix lever to match your application:

operate both motors from a 15-amp circuit

> Dust Extraction Mode: 235 CFM (airflow), 90" H20 (lifting power)

• 120 Volt, 5.83 Amp Motors (2) ~ Low amp draw, high efficiency motors,

> Sweep Mode: 123 CFM, 140" H20. Extreme lifting power, used to sweep floors after concrete grinding (dry or wet) or vacuuming heavy objects including water, dirt, rocks, sludge, slurry, etc.

• Cyclone deflector, cone filter, high efficiency (HE) pleated filter, Dacron filter cover (protects the filters, sheds fine dust and water), all three filters and the Dacron cover are washable.

• Air Pulse Collection Bag – pre-filter, keeps the above 3-filters clean

• Wet filter with float shut-off system - the above 4-filters are removed

 Very compact and portable — complete vacuum including the cart provides superior handling, maneuvering and transporting.

• Dimensions: 21.5" x 23.5" x 38", Weight: 47 lbs.

\$1,190.00

Equipment:

• 1.5" x 9' w/ 2" ID smooth cuff, professional wand and nozzle kit (crevice tool, floor sweep with brushes & squeegee, 2-part metal, 2-part plastic wands, hose end cuff), 3' flexible drain hose, Air Pulse bags (5).

CS235-BV — 2-Motor Barrel Vac, 45-Gal, 120V, Flow Mix: 235 CFM or 140" H20

Performance:

Filtration:

Equipment:



Power:

• 120 Volt, 5.83 Amp Motors (2) ~ Low amp draw, high efficiency motors, operate both motors from a 15-amp circuit

• Slide the Flow Mix lever to match your application:

> Dust Extraction Mode: 235 CFM (airflow), 90" H20 (lifting power)

> Sweep Mode: 123 CFM, 140" H20. Extreme lifting power, used to sweep floors after concrete grinding or to vacuum heavy debris such as water, dirt, rocks, sludge, slurry, etc.

as water, diff, rocks, sludge, sluffy, etc.

 Cyclone deflector, cone filter, high efficiency (HE) pleated filter, Dacron filter cover (protects the filters, sheds fine dust and water), all three filters and the Dacron cover are washable.

• Wet filter with float shut-off system - the above 3-filters are removed

45-Gal Capacity Metal Barrel, Powder Coated with 3" Drain-Gate; HD
Metal Swivel Dolly with 5-Rubber Casters, Powder Coated; Dual Wet/Dry
Filters (see above), 20" HD Aluminum Floor Sweep with 2" x 49" aluminum
wand, brush set & rubber squeegee (wheels, brushes, squeegee are
adjustable), 2" x 50' premium flex & durable hose with cuffs.

\$2,989.00

CS315-BV — 3-Motor Barrel Vac, 45-Gal, 120V, 2-Stage Motors: 315 CFM, 92" H20



Power:

 120 Volt, 7.75 Amp Motors (3), individual on/off switches, two power cords, operate two motors from a 15 amp circuit

Performance:

 Combination of 315 CFM & 92" H20 provides unmatched performance and motor life as a powerful wet / dry vac.

Filtration:

 Cyclone deflector, cone filter, high efficiency (HE) pleated filter, Dacron cover filter (protects the filters, sheds fine dust and water), all three filters are washable.

Wet filter with float shut-off system – the above 3-filters are removed

Equipment:

• Same as the above 2-Motor Barrel Vac, #CS235-BV.