



ADVANTAGE CONTRACTORS SUPPLIES

Concrete, Masonry, Dust Control Sales

24 39th Street, Pittsburgh, PA 15201

Phone: 412 . 687 . 5005

www.USAdustGuard.com

Price List: Epoxy Adhesive - Anchoring / Doweling PA DOT Bulletin 15 Approved

PRICE DATE: Oct 2018



MKT Liquid Roc 300

- > Twin Tube - Polyester Resin **Base**, Benzoyl Peroxide Hardener
- > Easy to use and can be saved for re-use, Works well in horizontal and overhead applications
- > 30 - 40 minute working time at 68°F to 80°F, 9 month shelf life
- > Useable in temperatures from 28°F to 110 °F
- > PA Bulletin 15, Section 516: Concrete Pavement Patching - 516.2(k) Anchor Material
- > **Safety Data Sheet, Estimating Guide, Submittal Generator** - all available online at:
<https://www.mktfastening.com/products/liquid-roc-300-twin-tube>

Size - Cartridge

28 oz

Case Qty

5 / Case

Case Price (Ea)

\$ 26.00

Pallet Price (Ea)

\$13.00 - 300 tubes

Dispensing Tools

7521095 (manual)

7521096 (pneumatic)

Price Ea

\$134.00

\$585.00

* Replacement Nozzles

7521041

\$ 2.00

Adhesives Technology Corporation

Ultrabond 365CC

- > All Season Hybrid Adhesive - Concrete & Masonry
- > High Strength, **Non-Sag** Epoxy for Threaded Rod, Rebar - Vertical, Horizontal, Overhead
- > Fast Cure - also approved for use in cracked and un-cracked concrete
- > Moisture insensitive allowing installation and curing in damp environments
- > In-Service temperature range from 5 °F to 302 °F — flexibility provides year-round installation
- > Full cure in 45 minutes at 77°F, 12 month shelf life, 3:1 mixing ratio
- > PA Bulletin 15, Section 516: Concrete Pavement Patching - 516.2(k) Anchor Material
- > **Safety Data Sheet, Estimating Guide, Submittal Generator** - all available online at:
<http://atcepoxy.com/ultrabond-365cc-adhesive>

Size - Cartridge

20 oz

Case Qty

12 / Case

Case Price (Ea)

\$29.20

Pallet Price (Ea)

\$19.95 - 504 tubes

Dispensing Tool

TM13-20 (manual)

Price Ea

\$ 79.00

* Replacement Nozzles

T-365CC-L

\$ 3.85

Adhesives Technology Corporation

Ultrabond 1300

- > High Strength, **Non-Sag** Epoxy for Threaded Rod & Rebar Dowels
- > Available in cartridge and bulk dispensing systems
- > Moisture insensitive allowing installation and curing in damp environments
- > 100% solvent free, zero VOC content - little or no odor, 1:1 mixing ratio
- > 20 minute working time at 75°F (24°C), 24 month shelf life
- > Useable in temperatures from 40 °F to 110 °F
- > PA Bulletin 15, Section 516: Concrete Pavement Patching - 516.2(k) Anchor Material
- > **Safety Data Sheet, Estimating Guide, Submittal Generator** - all available online at:
<http://atcepoxy.com/high-strength-non-sag-doweling-epoxy/>

<u>Size - Cartridge</u>	<u>Case Qty</u>	<u>Case Price (Ea)</u>	<u>Pallet Price (Ea)</u>
22 oz	12 / Case	\$19.00	\$14.70 - 576 tubes
53 oz	6 / Case	\$43.00	\$33.50 - 252 tubes
			\$30.00 - 3 pallet
<u>Tools</u>		<u>Price Ea</u>	<u>Free (included)</u>
TM22HD (manual)		\$ 78.00	3 each / pallet
TM22HD-A (pneumatic)		\$529.00	1 per 3 pallets
TM53HD-A (pneumatic)		\$529.00	1 per 3 pallets
<u>* Replacement Nozzles</u>			
T3438C4		\$ 2.60	

Ultrabond ASF-1000

- > Vinyl-ester resin (vs. polyester chemistry of Liquid Roc 300)
- > 18 month self life (vs. 9 month for Liquid Roc 300)
- > Cures down to 15° (vs. 28° for Liquid Roc 300)
- > Ultra-fast 30 minute full cure at 77 °F
- > Easy dispensing in low temperatures, wide service temperature range: -40 °F to 176 °F
- > Moisture insensitive allowing installation and curing in damp environments
- > PA Bulletin 15, Section 516: Concrete Pavement Patching - 516.2(k) Anchor Material
- > **Safety Data Sheet, Technical Data Sheet, Submittal Generator** - all available online at:
<http://atcepoxy.com/fast-curing-cold-weather-doweling-adhesive-asf-1000/>

<u>Size</u>	<u>Case Qty</u>	<u>Case Price (Ea)</u>	<u>Pallet Price (Ea)</u>
28 oz	8 / Case	\$19.50	\$14.00 - 384 tubes
<u>Tools</u>		<u>Price Ea</u>	<u>Free (included)</u>
TM28HD (manual)		\$ 92.00	3 each / pallet
TM28HD-A (pneumatic)		\$560.00	1 per 3 pallets
<u>* Replacement Nozzles</u>			
T14HGR		\$ 2.55	

* All cartridges include (1) mixing nozzle.

DeWALT - POWERS Corporation

AC 100+ GOLD

- > Two-Component Vinyl ester, Acrylic - High performance adhesive for threaded rod and reinforcing bars (rebar, smooth dowel bars) into drilled holes in concrete and masonry base materials
- > Versatile low odor formula with quick cure time
- > Permissible Installation Conditions: dry or water-saturated concrete (wet), water-filled holes (flooded)
- > Suitable Base Materials: normal-weight concrete, grouted concrete (CMU), hollow concrete masonry (CMU), brick masonry
- > Suitable for to resist loads in cracked or un-cracked concrete base materials
- > Size Range: 3/8" to 1-1/4" diameter threaded rod, No. 3 to No.10 rebar
- > Qualified for seismic (earthquake) and wind loading
- > 25 minute cure time, 4 minute working time at 86°F, 18 month shelf life
- > Useable in temperatures as low as 14°F
- > PA Bulletin 15, Section 516: Concrete Pavement Patching - 516.2(k) Anchor Material
- > [Safety Data Sheet, Estimating Guide, Submittal Generator](#) - all available online at: http://anchors.dewalt.com/anchors/submittal_generator/hemical-anchors

<u>Size - Cartridge</u>	<u>Case Qty</u>	<u>Case Price (Ea)</u>	<u>Pallet Price (Ea)</u>
28 oz	8 / Case	\$23.50	\$20.00 - 240 tubes
<u>Tools</u>		<u>Price Ea</u>	
08494-PWR (Manual)		\$ 70.00	
08496-PWR (pneumatic)		\$410.00	
DCE595D1 (20v cordless w 2.0 aH battery & charger)		\$295.00	
Replacement Batteries			
> DCB203 2.0 aH		\$ 90.34	
> DCB200 3.0 aH		\$106.75	
> DCB205 5.0 aH		\$132.88	
<u>* Replacement Nozzles</u>			
08294-PWR		\$ 3.52	

PURE 110+

- > Two-Component High Strength Epoxy - High performance adhesive for threaded rod and reinforcing bars (rebar, smooth dowel bars) into drilled holes in concrete and masonry base materials
- > Permissible Installation Conditions: dry or water-saturated concrete (wet), water-filled holes (flooded)
- > Suitable Base Materials: normal-weight concrete, grouted concrete (CMU), hollow concrete masonry (CMU), brick masonry
- > Suitable for to resist loads in cracked or un-cracked concrete base materials
- > Size Range: 3/8" to 1-1/4" diameter threaded rod, No. 3 to No.10 rebar
- > Qualified for seismic (earthquake) and wind loading
- > 8 hour cure time, 20 / 25 minute working time at 86°F / 68°F, 24 month shelf life
- > Cartridge temperature must be 50°F when being used, best at 68°F minimum
- > Not approved for PA DOT use - Bulletin 15
- > [Safety Data Sheet, Estimating Guide, Submittal Generator](#) - all available online at: http://anchors.dewalt.com/anchors/submittal_generator/hemical-anchors

<u>Size - Cartridge</u>	<u>Case Qty</u>	<u>Case Price (Ea)</u>	<u>Pallet Price (Ea)</u>
21 oz	12 / Case	\$25.50	\$21.90 - 540 tubes
<u>Tools</u>		<u>Price Ea</u>	
08409-PWR (Manual)		\$ 50.00	
DCE591D1 (20v cordless w 2.0 ah battery & charger)		\$295.00	
Replacement Batteries			
> DCB203 2.0 aH		\$ 90.34	
> DCB200 3.0 aH		\$106.75	
> DCB205 5.0 aH		\$132.88	
<u>* Replacement Nozzles</u>			
08609-PWR		\$ 4.70	

DeWALT - POWERS Corporation

AC 200+ GOLD

- > Two-Component Hybrid Acrylic - High performance adhesive for threaded rod and reinforcing bars (rebar, smooth dowel bars) into drilled holes in concrete and masonry base materials
- > Versatile low odor formula with quick cure time
- > Permissible Installation Conditions: dry or water-saturated concrete (wet), water-filled holes (flooded)
- > Suitable Base Materials: normal-weight concrete, grouted concrete (CMU), hollow concrete masonry (CMU), brick masonry
- > ICC-ES Approved for used in cracked and un-cracked concrete
- > Size Range: 3/8" to 1-1/4" diameter threaded rod, No. 3 to No.10 rebar
- > Seismic Approved for seismic (earthquake) design categories A - F
- > 30 minute cure time, 2 minute working time at 86°F, 18 month shelf life
- > Useable in temperatures as low as 23°F
- > Not approved for PA DOT use - Bulletin 15, Competitive Comparison: Hilti HY200 / 270
- > **Safety Data Sheet, Estimating Guide, Submittal Generator - all available online at:**
http://anchors.dewalt.com/anchors/submittal_generator/hemical-anchors

<u>Size - Cartridge</u>	<u>Case Qty</u>	<u>Case Price (Ea)</u>	<u>Pallet Price (Ea)</u>
28 oz	8 / Case	\$31.50	\$28.00 - 240 tubes
<u>Tools</u>		<u>Price Ea</u>	
08494-PWR (Manual)		\$ 70.00	
08496-PWR (pneumatic)		\$410.00	
DCE595D1 (20v cordless w 2.0 aH battery & charger)		\$295.00	
Replacement Batteries			
> DCB203 2.0 aH		\$ 90.34	
> DCB200 3.0 aH		\$106.75	
> DCB205 5.0 aH		\$132.88	
<u>* Replacement Nozzles</u>			
PFC1271150		\$ 1.75	