



CleanSpace® WORK Particulate Standard TM3 P3 Filter (Pk 3)

CleanSpace


Free the way you breathe"



| PRODUCT CODE | CS3002WORK |
|-----------------------------|--|
| PRODUCT NAME | CleanSpace WORK Particulate Standard TM3 P3 Filter (Pk 3) |
| DESCRIPTION | CleanSpace WORK particulate filters TM3 P3 are suitable for protection against airborne particulates (dust, mists, fumes) with a particulate filtration efficiency ≥ 99.97%. |
| | CleanSpace WORK filters are compatible with the CleanSpace WORK power unit (CS3001WORK). |
| | IMPORTANT: When selecting a CleanSpace filter please consult a Health and Safety specialist for advice on the appropriate respiratory equipment and filter use. |
| APPROVALS | Standard & Classification |
| | EN12942:1998+A2:2008 TM3 AS/NZS1716: 2012 PAPR-P3 (P2 with Half Mask) |
| FEATURES | Convenient to use |
| | Filter and filter cover integrated into a single item |
| | Easy to fit and remove from the power unit |
| | No requirement for a filter adaptor |
| | AirSensit[™] Technology assists with optimal filter usage. |
| SPECIFICATIONS | Packaged Weight & Dimensions: 123 g, 180mm x 160mm x 50mm (3 Pack) |
| | Product Weight & Dimensions: 29 g, 24mm x 47mm x 130mm (single filter) |
| | Filtration performance: ≥ 99.97% filtration efficiency for particulates |
| | Sold in a pack of 3 filters |
| MATERIALS | Borosilicate microfibre media ABS (acrylonitrile butadiene styrene) Plastic Casing Polyurethane Seal |
| USE & STORAGE CONDITIONS | Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity |
| | Storage conditions: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity |
| | Store away from direct sunlight, grease and oil |
| | Packaged Shelf life: 5 years from manufacturing date |
| APPLICATIONS | Suitable for environments which require respiratory protection against airborne particulate contaminates |

Australia (Head Office): +61 2 8436 4000 | sales@cleanspacetechnology.com

Uncontrolled if downloaded or printed from the internet.







DATA SHEET



Examples (use is not limited to these examples):

- Construction Cutting and grinding concrete, stone, brickwork, steel; sanding plaster, handing cement or other fine dusts
- Woodwork Cutting, turning or sanding timber
- Agriculture mowing, reaping and mulching operations; processing or handling animal feeds, grain
 or other dusty substances

The CleanSpace WORK System (CS3000WORK) is suitable for applications where decontaminations showers are used.

LIMITATIONS

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace WORK in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours, or in oxygen enriched or deficient atmospheres.

EDUCATION

Contact sales@cleanspacetechnology.com or visit the CleanSpace website for details.

WARRANTY

Visit www.cleanspacetechnology.com/warranty to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

CleanSpace recommends filters are replaced regularly.

Australia (Head Office): +61 2 8436 4000 | sales@cleanspacetechnology.com Uncontrolled if downloaded or printed from the internet.

