

USA

Dust Guard



FHWA - Buy America Manufactured Products

Div. of Scott Electric • 412-605-2992 (Direct)

PA Bulletin 15 Approved

The following adhesive products comply to the
Buy American Products Regulation.

And are available through USA Dust Guard,
a Division of Scott Electric USA.



For technical assistance & pricing, call: 412 - 605 - 2992

PA DOT Approvals - Made in USA Products

[Please call for Product Information & Approval Letter / Listing](#)

Adhesive Technology Corp

General Description

ULTRABOND HS-1CC

WORLD'S STRONGEST ANCHORING & DOWELING EPOXY

World's first anchoring epoxy formulated to be IBC/IRC compliant in both bulk and cartridge delivery systems. For use in dry, damp, water-filled and submerged applications, even in the most extreme temperatures and loading conditions — outperforms every other anchoring and doweling epoxy in the world.

ULTRABOND HS-200

HIGH-STRENGTH, EXTENSIVE DOT APPROVALS

Ideal for anchoring threaded rod, bolts and rebar dowels into concrete. With a long working time of 24 minutes and multiple embedment depth design tables, this anchoring epoxy offers a 2:1 mix ratio and a 28-month shelf life.

ULTRABOND 1300

HIGH-STRENGTH, NON-SAG DOWELING EPOXY

Smooth, non-sag, non-abrasive consistency ideal for use in bulk dispensing systems without adverse wear on pumps. Extensive DOT approvals. Available in cartridges and bulk.

ULTRABOND ASF-2000

FAST CURING COLD WEATHER DOWELING ADHESIVE

Domestically manufactured, two-component styrene free, acrylic adhesive used for anchoring and doweling applications in uncracked concrete with threaded rod and rebar. It is suitable for use in temperatures between 5°F and 110°F (-15°C to 43°C). Available in a 28 oz. cartridge.

CRACKBOND 2100 MV

MEDIUM VISCOSITY BONDING AGENT STANDARD & LONG POT LIFE FORMULAS

Two-component, high-strength epoxy adhesive that is ideal for bonding fresh to hardened concrete or perfect for use in a variety of repair projects.

CRACKBOND LR-321 LV

FORMULAS FOR VERSATILITY IN VARIOUS CRACK INJECTION APPLICATIONS

Crack injection epoxies with versatility for various high performance structural applications. LR-321 LV is a low viscosity epoxy for cracks that range from 1/8" to < 1/4", and LR-321 SLV is a super low viscosity epoxy for fine cracks up to 1/8". LR-321 TXO is a medium viscosity epoxy with unique thixotropic properties making it ideal for injection of blind-sided cracks > 1/4 in.

Dewalt / Powers

Pure 220+

Two-component, ultra high-strength adhesive anchoring system. Designed for bonding threaded rod and reinforcing bar hardware into drilled holes in concrete base materials and for post-installed reinforcing bar connections (rebar development). It can also be considered for anchor bolt repairs, filling abandoned holes and large cracks.