

# USA

# Dust Guard



# Stelli-Cutter

# Joint Sealant Cut-Out

Div. of Scott Electric • 412-605-2992 (#Direct)

## Sealant Slicer

### FAST REMOVAL – NO MELTING

### Remove Hard or Soft Sealant from Concrete Control Joints without Melting

### STELLITE CUTTERS MAINTAIN THEIR SHARP EDGE

- Traditional diamond segments GRIND which creates heat.
- The harden Stellite Cutters do not grind, they slice — *Prevents even soft joint sealant from melting!*
- **2 FOR 1:** Joint sealant is sliced from the control joint with one (1) pass of the blade, inside edges are scraped clean — *without melting the sealant!*



**Sealant is Cut Free • Inside Joint Edges are Bare • Joint is Prepped • Ready To Reseal**  
Incredible Blade Durability, Productivity, Results — **Nothing Is Faster & More Efficient**

ITEM NO	SIZE	PRICE EACH	
		Each	Box (5/bx)
91806	5" x 3/16 x 7/8"	\$149.00	\$ 129.00
91808	7" x 3/16 x DM-7/8"	\$239.00	\$204.00
380080	8" x 3/16 x DM-7/8"	\$ 289.00	\$ 250.00
91810	12" x 1/4 x 1" w Dr Hole	\$479.00	\$419.00

For use with angle grinders, joint saws, circular saws, walk-behind saws.

**DIRECTIONS:** Slice along the inside edge of the joint, pull the strip of sealant from the joint. If any

residual remains, use the cutter to remove it.

The harden Stellite cutters are protected from premature shattering even if concrete or mortar is

directly beneath the sealant.



Walkways, Driveways, Runways, Tile-Up Panels, etc. - Slice through hard and soft joint sealant materials without melting.



Polished Concrete Floors - Slice through hard Polyurea joint sealant without melting.